


#### INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : E04F 15/02, 15/04	A1	<ul> <li>(11) International Publication Number: WO 98/38401</li> <li>(43) International Publication Date: 3 September 1998 (03.09.98)</li> </ul>
(21) International Application Number: PCT/SE (22) International Filing Date: 10 February 1998 ( (23) Priority Data: 9700671-2 26 February 1997 (26.02.97 (71) Applicant (for all designated States except US): TARE [SE/SE]; S-289 89 Hanaskog (SE). (72) Inventor; and (75) Inventor/Applicant (for US only): STRIDSMAN, [SE/SE]; Fridhall, S-289 50 Hanaskog (SE).	10.02.9 ) :	BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Ulitis) model), DE, DE (Ulitily model), DE, M, DK (Ulitily model) EE, EE (Ulitily model), ES, FI, FI (Ulitily model), GB, GE GH, GM, GW, HU, ID, IL, IS, P, KE, KG, KP, KR, KZ LC, LK, IR, LS, LT, LU, LV, MD, MG, MK, MN, MM MX, NO, NZ, PI, -PT, RO, RU, SD, SE, SG, SI, SK, SI (Ulitily model), SL, TJ, TM, TR, TT, UA, UG, US, UZ VN, YU, ZW, ARPO patent (GH, GM, KE, LS, MY, BURSIAN) BS, Z, UG, ZW), Burnsian patent (AM, AZ, BY, KG, KZ MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK ES, FI, FR, GB, GR, IE, TI, LU, MC, NL, FT, SE), OA4 patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NR)
(74) Agent: AWAPATENT AB; P.O. Box 5117, S-200 7 (SE).	71 Mali	Deblished With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt amendments. In English translation (filed in Swedish).

### (54) Title: PARQUET FILLET

#### (57) Abstract

A rectangular parquet fillet (21) comprises at its edge surfaces a tongue-end-growe arrangement to be connected to other parquet fillets provided with tongue-and-grove arrangements in order to form a floor. The tongue-and-grove arrangement comprises a grove (22) in each terminal edge surface of the fillet (21), which grove extends over the whole width of the fillet. A first tongue (23) is arranged at one side edge surface of the fillet (21) and is positioned in one end portion of the fillet in an area extending from the terminal edge surface of the fillet (21) in this end portion along the fillet, a distance which is smaller than or equal to the width of the fillet. A tongue arrangement (25, 26, 28) is arranged at the other side edge surface of the fillet.



## FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL AM AT AU AZ BA BB BE BF BG BJ BR BY CA CF CG CH CI CM	Albania Armenia Armenia Anutria Austria Austria Austria Balanda Balanda Balanda Belgium Budian Faxo Bulgaria Benia Benia Benia Benia Congo Switzerland Côte d'Ivoire Cameroon	ES FI FR GAB GB GC GR HU IE IL IS IT JP KE KG	Spain Finland Finland Finne Georgi Georgi Georgi Ghana Guinea Giecec Guinea Greece Hungary Ireland Rely Japan Kenya Kyrgyzatan Democratic People's Republic of Korea	LS LT LU MC MD MG MK ML MN MR MV MX NE NL NO NZ PL	Lesotho Lishumia Lasembourg Latvin Monaco Kepublic of Moldova Madaguscer Vagoslav Kepublic of Mondova Madaguscer Moldova Madaguscer Moldova Madawi Mondowi Mon	SI SK SN SZ TD TG TIJ TM TR TT UA UG US VN YU ZW	Slovenia Slovenia Slovenia Senegal Sewalland Chad Topo Tujikatana Tudor Tukidatana Tukidaran Tukidatan Tukidaran Ukraine Uganda Ukraine Uganda Ukraine Uganda Zinbabara Zinbabara
CA	Canada	IT	Italy	MX NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL NO	Netherlands Norway		
CI CM	Côte d'Ivoire Cameroon	KP KR					
CN CU CZ	China Cuba Czech Republic	KZ LC	Kazakstan Saint Lucia	RO RU SD	Romania Russian Federation Sudan		
DE DK EE	Germany Denmark Estonia	LK LR	Sri Lanka Liberia	SE SG	Sweden Singapore		

10

15

20

25

30

### PARQUET FILLET

The present invention relates to a parquet fillet, which has a rectangular shape and which has at its edge surfaces a tongue-and-groove arrangement to be connected to other parquet fillets provided with tongue-and-fillet arrangements in order to form a floor, in particular a floor in which the fillets form a herring-bone pattern.

A portion of a parquet floor laid in a herring-bone pattern by means of prior-art parquet fillets of this type is shown in Fig. 1. These prior-art fillets are shown in more detail in Figs 2 and 3. The parquet fillets 1 are rectangular and have a tongue 2 at one side edge surface, a tongue 3 at one terminal edge surface, a groove 4 in the other side edge surface and a groove 5 in the other terminal edge surface. These tongues 2, 3 and grooves 4, 5 extend over the whole length of the respective edge surfaces. In order to lay a floor, in which the fillets 1 form a herring-bone pattern, by means of the prior-art fillets, they must be provided as left-hand fillets (L) and right-hand fillets (R), which differ only by being the reflected image of one another as regards the tongue-and-groove arrangement (cf. Figs 2 and 3).

The prior-art fillets 1 usually have a wearing layer, a bottom layer and an intermediate layer, which consists of a plurality of juxtaposed wood strips extending in the transverse direction of the fillet. The tongues 2, 3 and the grooves 4, 5 are formed in the intermediate layer. Since the direction of the wood fibres in the strips extends in the transverse direction of the fillet 1, the tongue 3 formed at the terminal edge surface of the fillet becomes fragile and easily breaks during the handling. In order to obviate this problem, this tongue 3 has been replaced by a groove and instead a loose tongue is used, which is positioned in this groove when laying the floor. By using a loose tongue in this

15

20

25

30

3.5

way, the need of two types of fillets (a left-hand and a right-hand fillet) has been eliminated. However, a disadvantage of this solution is that it is quite complicated to handle and mount loose tongues during the laying of the floor. Another more important disadvantage is that loose tongues result in an inferior alignment of the fillets than do the fixed tongues 3.

One object of the present invention is to provide a parquet fillet, which solves the above-mentioned problem without giving rise to the last-mentioned disadvantages.

According to the invention, this object is achieved by a parquet fillet of the type defined by way of introduction and characterised in that the tongue-and-groove arrangement comprises a groove in each terminal edge surface of the fillet, which groove extends over the whole width of the fillet, a first tongue at one side edge surface of the fillet, which tongue is positioned in one end portion of the fillet in an area extending from the terminal edge surface of the fillet in this end portion along the fillet a distance which is smaller than or equal to the width of the fillet, and a tongue arrangement at the other side edge surface of the fillet.

In a particularly simple embodiment, a groove extends along said one side edge surface of the fillet from the first tongue to the opposite terminal edge surface of the fillet and the tongue arrangement at said other side edge surface of the fillet consists of a second tongue extending over the whole length of the fillet.

In a preferred embodiment, the tongue-and-groove arrangement comprises a second tongue at said one side edge surface of the fillet, which tongue is positioned in the other end portion of the fillet in an area extending from the terminal edge surface of the fillet in this other end portion along the fillet a distance which is smaller than or equal to the width of the fillet, and a third and a fourth tongue at the other side edge surface of the fillet, which tongues are positioned in the first

20

25

30

35

and the second end portion, respectively, of the fillet in the same area as the first and the second tongue, respectively. At least one additional tongue is preferably arranged at each side edge surface between the first and the second tongue and between the third and the fourth tongue, respectively, the distance between the tongues at the respective side edge surfaces being greater than the width of the fillet.

The invention will now be described in more detail no with reference to the accompanying drawings.

Fig. 1 shows a portion of a parquet floor laid in a herring-bone pattern by means of the prior-art fillets that are described in more detail above.

Figs 2 and 3 show such a prior-art fillet on a larger scale, the fillet being shown with a left-hand and a right-hand design, respectively.

Fig. 4 shows a portion of a parquet floor laid in a herring-bone pattern by means of fillets according to the present invention.

Figs 5 and 6 show a fillet according to Fig. 4 on a larger scale, which fillet is shown with a left-hand and a right-hand design, respectively.

Fig. 7 shows a portion of a parquet floor laid in a herring-bone pattern by means of fillets according to the present invention, which fillets have a design different from that of the fillets shown in Figs 4-6.

Fig. 8 shows a fillet according to Fig. 7 on a larger scale.

The fillets 11 shown in Figs 5 and 6 are rectangular and have a tongue-and-groove arrangement at their edge surfaces. This tongue-and-groove arrangement comprises a groove 12 in each terminal edge surface of the fillet 11, which groove extends over the whole width of the fillet. The tongue-and-groove arrangement further comprises a first tongue 13 at one side edge surface of the fillet 11, which tongue is positioned in one end portion of the fillet in an area extending from the terminal edge sur-

15

face of the fillet 11 in this end portion along the fillet a distance which is smaller than or equal to the width of the fillet. The tongue-and-groove arrangement further comprises a groove 14 in the side edge surface where the first tongue 13 is positioned, and a second tongue 15 at the opposite side edge surface. The groove 14 extends from the first tongue 13 to the opposite terminal edge surface of the fillet 11. The second tongue 15 extends over the whole length of the fillet 11.

In order to make it possible to lay a floor, in which the fillets form a herring-bone pattern (see Fig. 4), the fillets 11 must be provided as left-hand fillets (L) and right-hand fillets (R), which are the reflected image of each other (cf. Figs 5 and 6). As is easily understood, in such a floor the terminal edge grooves 12 of the fillets 11 receive a first tongue 13 of an adjacent fillet.

The fillet 21 shown in Fig. 8 is also rectangular and has a tongue-and-groove arrangement at its edge surfaces. This tongue-and-groove arrangement, in conformity 20 with the tongue-and-groove arrangement of the fillet 11, comprises a groove 22 in each terminal edge surface of the fillet 21, which groove extends over the whole width of the fillet. The tongue-and-groove arrangement of the fillet 21 further comprises a first tongue 23 and a 25 second tongue 24 at one side edge surface of the fillet and a third tongue 25 and a fourth tongue 26 at the other side edge surface of the fillet. The first tongue 23 and the third tongue 25 are positioned in one end portion of the fillet 21 in an area extending from the terminal edge 30 surface of the fillet in this end portion along the fillet a distance which is smaller than or equal to the width of the fillet. The second tongue 24 and the fourth tongue 26 are positioned in the other end portion of the fillet 21 in an area extending from the terminal edge 35 surface of the fillet in this end portion along the fillet a distance which is smaller than or equal to the

10

15

20

width of the fillet. An additional tongue 27 is arranged at said one side edge surface of the fillet 21 between the first tongue 23 and the second tongue 24, and an additional tongue 28 is arranged at said other side edge surface of the fillet 21 between the third tongue 25 and the fourth tongue 26. The distance, i.e. the empty space, between the tongue 27 and the respective tongues 23, 24 and between the tongue 28 and the respective tongues 25, 26 is greater than the width of the fillet 21. A groove 29 extending between the respective tongues is formed in each of these spaces.

As is seen, the fillet 21 is symmetric both as regards its longitudinal and its transverse centre line. This results in the fillets 21 not having to be provided in special left-hand and right-hand designs.

As is easily understood, the terminal edge grooves 12 of the fillets, in a floor where the fillets 21 form a herring-bone pattern (see Fig. 7), receive the first, second, third or fourth tongue 23, 24, 25 and 26, respectively, of an adjacent fillet.

#### CLATMS


1. A parquet fillet, which has a rectangular shape and which has at its edge surfaces a tongue-and-groove 5 arrangement to be connected to other parquet fillets provided with tonque-and-groove arrangements in order to form a floor, in particular a floor in which the fillets form a herring-bone pattern, characterised in that the tongue-and-groove arrangement comprises a groove 10 (12; 22) in each terminal edge surface of the fillet (11; 21), which groove extends over the whole width of the fillet, a first tonque (13; 23) at one side edge surface of the fillet (11; 21), which tongue is positioned in one end portion of the fillet in an area extending from the 15 terminal edge surface of the fillet in this end portion along the fillet a distance which is smaller than or equal to the width of the fillet, and a tongue arrangement (15; 25, 26, 28) at the other side edge surface of the fillet. 20


2. A parquet fillet according to claim 1, c h a r - a c t e r i s e d in that a groove (14) extends along said one side edge surface of the fillet (11) from the first tongue (13) to the opposite terminal edge surface of the fillet, and the tongue arrangement at said other side edge surface of the fillet (11) consists of a second tongue (15) extending over the whole length of the fillet.


3. A parquet fillet according to claim 1, c h a r - 30 a c t e r i s e d in that the tongue-and-groove arrangement further comprises a second tongue (24) at said one side edge surface of the fillet (21), which tongue (24) is positioned in the other end portion of the fillet in an area extending from the terminal edge surface of the fillet in this other end portion along the fillet a distance which is smaller than or equal to the width of the fillet, and a third and a fourth tongue (25 and 26) at


the other side edge surface of the fillet (21), which tongues (25, 26) are positioned in the first and the second end portion, respectively, of the fillet in the same area as the first and the second tongue, respectively (23 and 24).


4. A parquet fillet according to claim 3, c h a r a c t e r i s e d in that at least one additional tongue (27, 28) is arranged at each side edge surface between the first and the second tongue (23 and 24) and between the third and the fourth tongue, (25 and 26), respectively, the distance between the tongues at the respective side edge surfaces being greater than the width of the fillet (21).











### INTERNATIONAL SEARCH REPORT

International application No.

	PCT/SE 98/	00223
A. CLASSIFICATION OF SUBJECT MATTER		
IPC6: E04F 15/02, E04F 15/04 According to International Patent Classification (IPC) or to both nat	tional classification and IPC	
B. FIELDS SEARCHED		
Minimum documentation searched (classification system followed by	classification symbols)	
IPC6: E04F		
Documentation searched other than minimum documentation to the	extent that such documents are included	in the fields searched
SE,DK,FI,NO classes as above		
Electronic data base consulted during the international search (name	of data base and, where practicable, sear	ch terms used)
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category* Citation of document, with indication, where app	ropriate, of the relevant passages	Relevant to claim No.
A US 2015813 A (H.C. NIELSEN), 1 0 (01.10.35), figures 1,2, det	ctober 1935	1-4
A US 2187672 A (A.G.W. WEDBERG), 1 (16.01.40), detail 14	6 January 1940	1-4
A US 3436888 A (P.A.R. OTTOSSON), (08.04.69), detail 11	8 April 1969	1-4
A WO 9700364 A1 (BRøDRENE FÜRST A/ (03.01.97), figure 2, abstra	(S), 3 January 1997 act	1-4
Further documents are listed in the continuation of Box	C. X See patent family ann	ex.
Special categories of cited documents:     A document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the i date and not in conflict with the ap the principle or theory underlying t	plication but cited to understand ne invention
"E" critic document but published on or after the international filling date  "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other	"X" document of particular relevance: ti considered novel or cannot be cons step when the document is taken also	dered to involve an inventive
special reason (as specified)  "O" document referring to an oral disclosure, use, exhibition or other means  "P" document published prior to the international filing date but later than the priority date claimed	"Y" document of particular relevance: to considered to involve an inventive: combined with one or more other second or object to a person skilled in "&" document member of the same pate."	tep when the document is uch documents, such combination the art
Date of the actual completion of the international search	Date of mailing of the international	
11 has 1000	2 4 -06- 1	398
11 June 1998  Name and mailing address of the ISA/	Authorized officer	
Swedish Patent Office Box 5055, S-102 42 STOCKHOLM	Örjan Nylund	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No. 29/04/98 PCT/SE 98/00223

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2015813 A	01/10/35	NONE	
US 2187672 A	16/01/40	NONE	
US 3436888 A	08/04/69	DE 1684056 A DK 122900 B FI 43006 B SE 301705 B	13/01/72 24/04/72 02/09/70 17/06/68
WO 9700364 A1	03/01/97	AU 6140296 A NO 300387 B NO 952349 A	15/01/97 20/05/97 16/12/96